C-18 OR C-23 SIGN

C-13 OR C-14 SIGN

S See TABLE "A"

BARRICADE

C-18 OR C-23 SIGN

C-13 OR C-14 SIGN

50' Min. Gap Between Delineators

CURB OR E.P.

S See Table "A"

C-18 OR C-23 SIGN

WORK AREA

10' Min.

R-96 SIGN

CURB OR E.P.

INSTALL TEMPORARY NO PARKING SIGNS

Taper L (If Required)

S S S

See Table "A" See Table "A"

See Table "A"

C-20 (RT) SIGN

FLASHING ARROW BOARD

R-18 (RT) SIGN

R-96 SIGN

C-13 OR C-14 SIGN

50' Min. Tang.

INSTALL TEMPORARY NO PARKING SIGNS (If Required)

Taper L

See Table "A"

50' Min. Gap Between Delineators

BARRICADES

HIGH LEVEL WARNING DEVICE W/ C-30 SIGN

FLASHING ARROW BOARD

CURB OR E.P.

C-20 (LT) SIGN

C-18 OR C-23 SIGN

C-13 OR C-14 SIGN

S See Table "A"

S See Table "A"

S See Table "A"

LANE CLOSED

C30

ROAD CONSTRUCTION AHEAD

C18

ROAD WORK AHEAD

C23

END CONSTRUCTION

C13

END ROAD WORK

C14

CENTER OR RIGHT

NO. OF LANES

LEFT LANE CLOSED AHEAD

C20

LEGEND

- Traffic Cone or Delineator
- Sign
- Direction of Travel (Not a pavement marking)
- Flashing Arrow Board (Where Required)
- High Level Warning Device (Flagtree)
- Barricade (For Excavation Only)
- Flagger

SEE TABLE "A" FOR SIGN, CONE SPACING AND TAPER LENGTH

SPEED	APPROACH STREET	TAPER LENGTH	SIGN SPACING

INDICATE NORTH WITH A "N" AND AN ARROW POINT

WORKSITE TRAFFIC CONTROL PLAN
WORK WITHIN INTERSECTION
RIGHT LANE / LEFT LANE

DATE		SCALE
05/06/2003 Rev. MPL		NONE
05/27/2003 WRS		DRAWING NO. 9